


Type:	MK-LXS6	REV: 0
Issued:	19/10/2021	KP
Project:	079-21_01	

MetroJET MK-LXS6 - Multi loose tube microcable (up to 72F)



*Schematic drawing, not to scale

APPLICATION:

Microduct cabling air-blowing system application
 Metro networks
 Flexible network design
 Distribution network

DESIGN:

HDPE, UV stabilized outer jacket with low coefficient of friction
 Loose tubes (and fillers), SZ stranded around the FRP
 Each PBT tube containing up to 12 optical fibres
 Smallest outer diameter for blowing into 8mm (ID) ducts

CABLE DESIGNS:

Variant	Quantity pcs				Ø nominal (±5%) mm	Nominal weight (±10%) kg/km
	Fibres	Fibres per tube	Total elements	Active tubes		
1-6T x 2F	2-12	2	6	1-6	5.3	18
1-6T x 4F	4-24	4	6	1-6	5.3	18
1-6T x 6F	6-36	6	6	1-6	5.3	18
1-6T x 8F	8-48	8	6	1-6	5.3	19
1-6T x 10F	10-60	10	6	1-6	5.3	19
1-6T x 12F	12-72	12	6	1-6	5.3	21

APPLICATION:

Suggested duct - Ø (min)	16/12 mm, 14/12 mm, 12/10 mm, 14/10 mm, 12/8 mm, 10/8 mm				
Temperature range	Transport & Storage:	- 40 to + 70 °C	Minimum Bending Radius		
	Installation:	- 15 to + 55 °C		Under maximum tension:	15 x cable Ø
	Operation:	- 40 to + 70 °C		Without tension:	10 x cable Ø

MAIN MECHANICAL AND ENVIRONMENTAL CHARACTERISTICS

Test	Test Standard	Specified Value	Requirement
Max allowed tension	IEC60794-1-21 Method E1	Load: 650 N	$\Delta\epsilon_r \leq 0.33\%$, $\Delta\alpha$ reversible No significant damage to fibre unit
Max operating tension		Load: 200N	$\Delta\epsilon_r \leq 0.05\%$, $\Delta\alpha \leq 0.05$ dB/km No significant damage to fibre unit
Crush	IEC 60794-1-21 Method E3	Short term: 1000 N / 100 mm, 1 min Long term: 500 N / 100 mm, 15 min	$\Delta\alpha$ reversible, No significant damage to fibre unit
Impact	IEC 60794-1-21 Method E4	Impact energy: 10J, 3 impacts, R= 300 mm	$\Delta\alpha \leq 0.05$ dB/km after the test No jacket cracking and fibre breakage
Torsion	IEC 60794-1-21 Method E7	Cable length to be twisted: 2m No. of cycles: 10 Twist angle: $\pm 180^\circ$	$\Delta\alpha \leq 0.05$ dB/km, No jacket cracking and fibre breakage
Repeated bending	IEC 60794-1-21 Method E6	Sheave Radius: 10 x OD	No jacket cracking and fibre breakage
Cable bend	IEC 60794-1-21 Method E11	Mandrel radius: 15 x OD / 4 turns / 3 cycles	$\Delta\alpha \leq 0.05$ dB/km, No jacket cracking and fibre breakage

Type:	MK-LXS6	REV: 0
Issued:	19/10/2021	KP
Project:	079-21_01	

Temperature cycling	IEC 60794-1-22 Method F1	1st cycle: +23 °C → -30 °C(Ta1) → +60 °C(Tb1) → -40 °C(Ta2) → +70 °C(Tb2) 2nd cycle: -30 °C(Ta1) → -40 °C(Ta2) → +60 °C(Tb1) → +70 °C(Tb2) → +23 °C Soak time: 8 h	For TA2 and TB2 $\Delta\alpha \leq 0,05$ dB/km For TA1 and TB1 $\Delta\alpha \leq 0,05$ dB/km
Water penetration	IEC 60794-1-22 Method F5B	Water head: 1 m Sample length: 3 m Time: 24 hrs	No water leakage

(*) values for single-mode fibres, all optical measurements performed at @1550nm

OPTICAL FIBRE AND LOOSE TUBES COLOUR IDENTIFICATION

For optical fibres and loose tube identification information please see DSH_Colors_CODE_XXXX document.

FIBRE PARAMETERS

For selected post-production optical fibres parameters please see DSH_OFPP document.

MARKING

The following print (inkjet / laser or other suitable method) is applied at 1-meter intervals

- Supplier: FIBRAIN METROJET
- Standard code (Product type, fibre type, fibre count)
- Year of manufacture: xxxx
- Length marking in meters
- Cable ID / Drum No

Example: METROJET MK-LXS6 72F SM G652D 6T12F "YEAR OF MANUFACTURE" "LASER SYMBOL" "LENGTH MARKING" "BATCH NUMBER"

The accuracy of marking is $\pm 0,5\%$. Remarking is in accordance with Bellcore GR 20 and supersedes earlier markings. Occasional loss of marking is possible. Cables can be supplied with a range of single mode or multimode fibres and customized print.

PACKING

Cables will be shipped on disposable wooden or treated wooden drums. Both ends of the cable will be capped and accessible for testing. Identification information label will be placed on the drum.

DELIVERY LENGTH

2000 – 8000 meters $\pm 5\%$, with possibility of supplying up to 5% of total contract quantity as short length cables which should be above 1000 meters long. Tolerance of 5 % of order quantity shall be allowed.

This document and the statements contained in it are not intended for customers within the meaning of the Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot, in any case, be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.