


Type:	Metrojet MK-LXS-TKT	REV: 0
Issued:	19/10/2021	KP
Project:	079-21	

MetroJET MK-LXS-TKT - Multi loose tube microcable



*Schematic drawing, not to scale

APPLICATION:

Microduct cabling air-blowing system application
 Metro networks
 Flexible network design
 Distribution network

DESIGN:

HDPE, UV stabilized outer jacket with low coefficient of friction
 Loose tubes (and fillers), SZ stranded around the CSM
 PBT tubes containing up to 12 optical fibres

CABLE DESIGNS:

Variant	Quantity [pcs]				Ø nominal (±5%) [mm]	Nominal weight (±10%) [kg/km]
	Fibres	Fibres per tube	Total elements	Active tubes		
1Tx6F G.655 + 2T12F G.652D + 4T6F G.652D + 3T4F G.652D	66	4 / 6 / 12	10	10	7.0	43

APPLICATION:

Suggested Duct - Ø (min)	mm	16/12mm, 14/12mm, 12/10mm, 14/10mm			
Temperature Range	Transport & Storage:	- 40 to + 70°C	Minimum Bending Radius		
	Installation:	-15 to + 55°C		Under Maximum Tension:	20 x cable Ø
	Operation:	- 30 to + 70°C		Without Tension:	10 x cable Ø

MAIN MECHANICAL AND ENVIRONMENTAL CHARACTERISTICS (according to IEC 60794-5)

Test	Test Standard	Specified Value	Requirement*
Max allowed tension	IEC 60794-1-21-E1	1500 N	$\Delta\epsilon \leq 0.33\%$, $\Delta\alpha$ reversible
Max operating tension	IEC 60794-1-21-E1	550 N	$\Delta\epsilon \leq 0.05\%$, $\Delta\alpha \leq 0.05$ dB/km
Crush	IEC 60794-1-21-E3	600 N / 100 mm, max. 15 min	$\Delta\alpha$ reversible, no significant damage
Impact	IEC 60794-1-21-E4	10Nm, 3 impacts, R= 300 mm	$\Delta\alpha \leq 0.05$ dB after the test
Torsion	IEC 60794-1-21-E7	100N, +/- 180°, 10 cycles	$\Delta\alpha \leq 0.05$ dB, no damage
Repeated Bending	IEC 60794-1-21-E6	R=20x D, 100N, 35 cycles	no damage
Cable Bend	IEC 60794-1-21-E11	R=20x D, 4 turns, 3 cycles	$\Delta\alpha \leq 0.05$ dB, no damage
Temperature Cycling	IEC 60794-1-22-F1	-15°C to +60°C -30°C to +70°C	$\Delta\alpha \leq 0.05$ dB/km $\Delta\alpha \leq 0.10$ dB/km
Water Penetration	IEC 60794-1-22-F5B	sample=3m, water column=1m, 24h	no water leakage

(*) values for single-mode fibres, all optical measurements performed at @1550nm

OPTICAL FIBRE AND LOOSE TUBES COLOUR IDENTIFICATION

For optical fibres and loose tube identification information please see DSH_Colors_CODE_XXXX document.

FIBRE PARAMETERS

For selected post-production optical fibres parameters please see DSH_OFPP document.

Type:	Metrojet MK-LXS-TKT	REV: 0
Issued:	19/10/2021	KP
Project:	079-21	

MARKING

The following print (inkjet / laser or other suitable method) is applied at 1-meter intervals:

FIBRAIN METROJET MK-LXS-TKT 66F SM G655 1T6F + G652D 2T12F + G652D 4T6F + G652D 3T4F HAWE TELEKOM tel. 61 86-14-935 "YEAR OF MANUFACTURE"
"LASER SYMBOL" "LENGTH MARKING" "BATCH NUMBER"

The accuracy of marking is $\pm 0,5\%$. Remarking is in accordance with Bellcore GR 20 and supersedes earlier markings. Occasional loss of marking is possible. Cables can be supplied with a range of single mode or multimode fibres and customized print.

PACKING

Cables will be shipped on disposable wooden or treated wooden drums. Both ends of the cable will be capped and accessible for testing. Identification information label will be placed on the drum.

DELIVERY LENGTH

2000 – 8000 meters $\pm 5\%$, with possibility of supplying up to 5% of total contract quantity as short length cables which should be above 1000 meters long. Tolerance of 5 % of order quantity shall be allowed.

This document and the statements contained in it are not intended for customers within the meaning of the Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot, in any case, be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.