


Type:	SSC-T30U LSOH	REV: 0
Issued:	28/09/2021	KP
Project:	079-21	

Single jacket cable with central tube, glass yarn reinforcement, and corrugated steel armouring SSC-T30U



*schematic drawing, not to scale

APPLICATION:

For installation into existing duct or directly buried
Rodent retardant

DESIGN:

Loose tube (PBT Ø 3.0mm) with filing compound
Fibre type: OM1
Fiberglass yarns as strain relief
Corrugated steel tape armouring
LSOH sheath (black or grey by default, other colours available)

CABLE DESIGNS:

Variant	Quantity [pcs]				Ø nominal (±5%) [mm]	Nominal weight (±10%) [kg/km]	Max short term tensile load [N]	Max long term tensile load [N]
	Fibres	Fibres per tube	Total elements	Active tubes				
1T x 2-24F LSOH	2-24	2-24	1	1	7,6	84	1500	750

Other designs available on demand

MECHANICAL AND ENVIRONMENTAL CHARACTERISTICS

Crush performance:	3000 [N/10 cm]	IEC 60794-1-21-E3, Δα reversible
Bending radius:	Static: 20 x D Dynamic: 30 x D	IEC 60794-1-21-E6, Δα≤0,05 dB
Water penetration:	3[m] sample, 1[m] head, 24[h]	IEC 60794-1-22-F5, no leakage
Temperature range		IEC 60794-1-22-F1, Δα≤0,05 dB/km
Installation:	-15... +50 [°C]	
Operation:	-40... +55 [°C]	
Transport & Storage:	-40... +60 [°C]	
CPR class	E _{CA}	EN 50575:2014+A1:2016

OPTICAL FIBRE AND LOOSE TUBES COLOUR IDENTIFICATION

For optical fibres and loose tube identification information please see DSH_Colors_CODE_XXXX document.

FIBRE PARAMETERS

For selected post-production optical fibres parameters please see DSH_OFP document.

Type:	SSC-T30U LS0H	REV: 0
Issued:	28/09/2021	KP
Project:	079-21	

MARKING

The following print (inkjet printer) is applied at 1-meter intervals:

WEEK/YEAR FORT FIBRE OTTICHE - COT1-AC/"FIBRE COUNT"MM625/LSZH + "SEQUENTIAL METER MARKING" + LF "BATCH NR." -Class Eca (EU-CPR305/11)

Example:

28/2019 FORT FIBRE OTTICHE - COT1-AC/8MM625/LSZH 00001m LF 9016/1 -Class Eca (EU-CPR305/11)

The accuracy of marking is $\pm 1\%$. Remarking is in accordance with Bellcore GR 20 and supersedes earlier markings. Occasional loss of marking is possible. Cables can be supplied with a range of single mode or multimode fibres and customized print.

PACKING

Cables will be shipped on disposable wooden or treated wooden drums. Both ends of the cable will be capped and accessible for testing. Rotation direction arrow will be marked on the drum together with identification information.

DELIVERY LENGTH

2000 meters $\pm 5\%$, with possibility of supplying up to 5% of total contract quantity as short length cables which should be above 1000 meters long. Tolerance of 5 % of order quantity shall be allowed.

This document and the statements contained in it are not intended for customers within the meaning of the Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot, in any case, be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.